

INFUSION PUMP VP3



Fitur

- 5 mode titrasi (Rate, Time, Dose, Sequential dan Drug Library)
- Titrasi bolus secara manual atau otomatis.
- Pemasangan dengan mounting clamp secara vertical atau horisontal.
- Dilengkapi fitur KVO (Keep Vein Open).
- Tampilan layar TFT berwarna yang dapat diatur tingkat kecerahannya
- Operasionalisasi yang mudah dengan Sistem tombol DPS.

KEMENKES RI AKD 20902321908

Didistribusikan oleh :

PT INDOPRIMA BIONET
Medical Equipment Supplier

Jl. Taman sari Raya, Komplek 56 No.56 B, Jakarta Barat 11150,
Telp : (+62-21) 649 5177, Fax : (+62-21) 649 2677
www.indoprimabionet.co.id

Spesifikasi teknis Indoprima Medical Infusion Pump VP3

PARAMETER	SPESIFIKASI
Set infus	Semua merk, setelah kalibrasi
Tingkat akurasi	$\pm 2\%$
Rentang kecepatan aliran	0.1ml/h~1200ml/h(0.1ml step)
Rentang waktu pemberian	00h01min ~ 99h59min (1 min step)
Rentang volume	0.0-9999ml (1 ml step)
Rentang volume total	0.0-9999ml (1 ml step)
Mode Dose	Volume :0.1-999.9ml(0.1ml step) Massa Obat :0.1-999.9mg (0.1mg step) Dosis :0.001-9999ug/kg/min(0.001ug/kg/min step) Berat Badan :0.1-300kg(0.1kg the least step)
Mode Drug Library	Tersedia
Mode Sequential	Tersedia
Rata-rata aliran KVO	0.0~5.0ml/h. (dapat diatur)
DPS Occlusion Pressure	LOW:60 \pm (15) kPa MEDIUM:90 \pm (15) kPa HIGH:120 \pm (15) kPa (Adjustable)
Alarm	Rate Abnormal , Door Open , Air-in-line , Occlusion , Bottle Empty , Battery Empty,No Battery,Key Holding During Infusion/Pause, Infusion Complete,No Action,Battery Low
Volume Alarm	Tiga Tingkat: Low, Medium, atau High
Fungsi Bolus	Bolus Rata-rata : 1.0~1200ml/h, Bolus volume:1.0~100ml Automatic/Manual, dapat diatur
Purge Rate	Dapat diatur
Konektivitas	RS-232
Kecerahan	Tingkat 1~10
Catatan Rekaman	2000 data (dapat dilihat & didownload)
Sumber Tenaga	AC power supply:AC 100 to 240V(+/-10%) , 50/60Hz; DC Power supply:12~15V, power>15W; Built-in Lithium Battery: Rechargeable, 11.1V, 2000mAh. 12 hours of continuous operation
Protection Class	Class I, Type CF,IPX4
Dimensi	120mm*100mm*215mm , 1.7kg
Dimensi Kemasan	250mm*190mm*155mm , 2.5kg
Optional	- Koneksi LAN - Drop Sensor